



## Water Quality Sonde with Flexible Sensor Payload

- **Product type**  
Attended, Unattended
- **Parameters measured**  
Temperature, Conductivity, Depth, pH, Oxygen Reduction Potential (ORP), Dissolved Oxygen (LDO), Dissolved Oxygen (Clark Cell), Turbidity, Chlorophyll a, Blue-Green Algae, Rhodamine WT, Ammonium, Nitrate, Chloride, Total Dissolved Gas (TDG), Ambient Light
- **Product Highlights**  
The Hydrolab sonde with the most available sensors
- **Interface**  
SDI-12, RS-485, RS-232, TTY

The Hydrolab DS5 multiparameter water quality sonde offers for maximum capability and flexibility the choice of any of Hydrolab's 17 superior sensors for either profiling or unattended monitoring.

<b>Sensors</b>	Measures up to 16 parameters simultaneously Capable of measurements using any of Hydrolab's 17 sensors
<b>Electrical</b>	
Internal	8 C batteries (with available internal battery pack option)
Communications	RS-232, SDI-12, RS-485
Memory	Up to 120,000 measurements

# Technical Data

Hydrolab DS5 - Multiparameter Data Sonde



## User Interface

PC Software	Hydras3 LT
Pocket PC Software	(Optional) TDS Recon with Hydras 3 LT Pocket

## General

Sonde Depth Rating	200 m (656 ft)
Diameter	8.9 cm (3.5 in.)
Weight	3.35 kg (7.4 lb) (typical)
Length	51.43 cm (23 in.)

## Environmental conditions

Operating temperature	-5 ... 50 °C (23 ... 122 °F), non-freezing
-----------------------	--------------------------------------------