



Non-contact, bubbler sensor for longterm surface water level monitoring

- **Application**
Eaux de surface, Débitmétrie
- **Measurement range**
Bubbler-in
- **Product Highlights**
Drift-free water level measurement - no pressure sensor or electronics in the water
- **Rango de medición**
0 to 15 m or 0 to 30 m
- **Accuracy**
 ± 3 mm (high accuracy version); ± 5 mm (standard and 30 meter versions)
- **Internal data logger**
1
- **Interface**
SDI-12, RS-485 (using SDI-12), or 4 ...20 mA

The OTT CBS is a compact, accurate, and low power bubbler sensor for surface water level monitoring. The OTT CBS meets or exceeds USGS standards for accuracy, and will not drift over time. It features outputs for SDI-12 and 4...20 mA.

Technical Data

OTT CBS - Compact Bubbler Sensor



Water level measurement

Measuring range

Version "Standard" and "USGS specification"	0 ... 15 m (0...50 ft)
Version "30 m measuring range"	0 ... 30 m (0...100 ft)
Resolution	1 mm (0.01 ft)
Accuracy	
Version "Standard" and "30m measuring range"	±5 mm
Version "USGS specification"	0 ... 15 ft: ±0.01 % 15 ... 50 ft: ±0.065 % of measurement value or 0.02 ft, whichever is less
Units	m, ft, bar, PSI

Electrical data

Interfaces	4 ... 20 mA, SDI-12, SDI-12 via RS-485
Power supply	10 ... 30 V DC, typ. 12/24 V DC

Current consumption

Measuring interval 1 min	typ. 320 mAh/day
Measuring interval 15min	typ. 25 mAh/day

Housing material ABS

Dimensions L x W x H 165 mm x 205 mm x 115 mm

Weight approx. 1,500 g

Protection class IP43

Environmental conditions	
Operating temperature	-20 ... +60 °C
Storage temperature	- 40 ... +85 °C
Relativ air humidity	10 ... 95 %; not condensing

Measuring tube inner diameter typ. 2 mm or 4 mm

EMV - limit values According to IEC61326 and EN61326