



Pressure probe with conductivity measurement cell

- **Application**
Eaux de surface, Débitmétrie
- **Measurement range**
Vented pressure cell and 4-electrode graphite conductivity cell
- **Parameters measured**
Water level, Pressure, Conductivity, Temperature
- **Product Highlights**
Water level, temperature, and conductivity measurement - for use with external data logger
- **Internal data logger**
1
- **Interface**
SDI-12 or RS-485 (using SDI-12)

The OTT PLS-C measures water conductivity, level, and temperature in both surface and groundwater applications with a robust ceramic pressure cell and 4-electrode conductivity cell. Its extremely low power consumption makes it ideal for long-term deployment, particularly at solar powered measuring stations for ground-and surface waters.

Output parameters

Water level/pressure, temperature, specific conductivity, salinity, TDS

Water level measurement (pressure)

Pressure sensor	ceramic, temperature-compensated
Measuring range	0 ... 4 m, 0 ... 10 m, 0 ... 20 m, 0 ... 40 m, 0 ... 100 m water col.
Resolution	0.001 m; 0.1 cm; 0.01 ft; 0.1 mbar; 0.001 psi
Accuracy (linearity + hysteresis)	$\leq \pm 0.05\% \text{ FS}$
Long-term stability (linearity + hysteresis)	$\leq \pm 0.1\% \text{ a FS}$
Zerodrift	$\leq \pm 0.1\% \text{ FS}$
Pressure sensor capability to withstand overloads without permanent mechanical damage	$\geq 4 \times$ measuring range
Temperature-compensated operating range	-5 °C ... +45 °C (ice free)
Units	m, cm, ft, mbar, psi

Temperature measurement

Sensor	NTC
Measuring range	-25 °C ... +70 °C (ice free)
Calibrated range	+5 °C ... 45 °C
Resolution	0.01 °C
Accuracy	$\pm 0.1\text{ }^{\circ}\text{C}$
Units	°C, °F

Conductivity measurement

Sensor	4 graphite electrodes
Calibrated range	+5 °C ... 45 °C

Measuring range 5 ... 2.000

μS/cm	
Resolution	1 μS/cm
Accuracy	$\pm 1 \mu\text{S}/\text{cm}$ or $\pm 0.5\%$ of measured value (whichever is higher)
Unit	μS/cm

Measuring range 0.1 ... 100

Resolution	0.01 mS/cm
Accuracy	$\pm 0.01 \text{ mS}/\text{cm}$ or $\pm 1.5\%$ of measured value (whichever is higher)
Unit	mS/cm

Options

Temperature compensation, conductivity	freshwater, saltwater, standard method 2510, ISO 7888/EN27888
Salinity calculation	Standard method or USGS 2311

Electrical data

Technical Data

OTT PLS-C



Supply voltage	6 ... 27 V DC, typically 12/24 V DC
Power consumption	
SDI-12 sleep-mode	<30 µAV
SDI-12 active-mode	<32 mA
Interfaces	
SDI-12, RS-485 (SDI-12 protocol)	
Mechanical data	
Dimensions	
Probe (Ø x h)	317 mm x 22 mm
Cable length	SDI-12: 1 ... 100 m RS-485: 1 ... 1000 m
Material	
Housing material probe	POM, stainless steel (DIN 1.4539, 904 L), resistant to sea water
Cable jacket	PUR
Weight	
Probe	approx. 0.43 kg
Probe cable	approx. 82 g/m
Ambient conditions	
Storage temperature	- 40 °C ... + 85 °C
Type of protection	Probe: IP 68
EMC limits	EG 2004/108/EG, EN 61326-1:2013